

25.04.2008 17:20 - 25.04.2008 18:05



	IP- ■	■	■	■	■	
	Cisco IP SLA G. 711a					
IP SLA G 711a [10.0.3.252->62.61.7.2] SNMP Device Availability (%)	>=99 100%	<99 0%	<96 0%	<94 0%	<90 0%	44
IP SLA G 711a [10.0.3.252->62.61.7.2] MOS	>=4 68,2%	<4 31,8%	<3 0%	<2 0%	<1 0%	44
IP SLA G 711a [10.0.3.252->62.61.7.2] ICPIF	<=5 47,7%	>5 15,9%	>10 36,4%	>30 0%	>45 0%	44
IP SLA G 711a [10.0.3.252->62.61.7.2] Delay (usec)	<=225 000 100%	>225 000 0%	>250 000 0%	>310 000 0%	>380 000 0%	44
IP SLA G 711a [10.0.3.252->62.61.7.2] PacketLoss (%)	<=1 50%	>1 9,09%	>2 6,82%	>3 11,4%	>5 22,7%	44
IP SLA G 711a [10.0.3.252->62.61.7.2] Jitter (usec)	<=50 000 29,5%	>50 000 47,7%	>60 000 20,5%	>80 000 0%	>100 000 2,27%	44
IP SLA G 711a [10.0.3.252->62.61.7.2] The Number of Round Trip Operations	>=95 9,09%	<95 22,7%	<85 9,09%	<70 9,09%	<50 50%	44
	IP- ()	0%	→→→ 4,55%	→→→ 6,82%	→→→ 27,3%	44

/ ProLAN; (www.prolan.ru/ta).
+7 (495) 933-12-89, (495) 913-30-67, sales@prolan.ru.

ЭЛИТАРНОЕ ДОСТУПНО



www.prolan.ru/services

