

25.04.2008 17:20 - 25.04.2008 18:05

PROLAN

	IP-	Cisco IP SLA	G. 711u			
	■	■	■	■	■	
IP SLA G 711u [10.0.3.252->62.61.7.2] SNMP Device Availability (%)	>=99 100%	<99 0%	<96 0%	<94 0%	<90 0%	44
IP SLA G 711u [10.0.3.252->62.61.7.2] MOS	>=4,4 0%	<4,4 88,6%	<3,6 11,4%	<3,1 0%	<2,6 0%	44
IP SLA G 711u [10.0.3.252->62.61.7.2] ICPIF	<=10 59,1%	>10 25%	>20 15,9%	>30 0%	>45 0%	44
IP SLA G 711u [10.0.3.252->62.61.7.2] Delay (usec)	<=225 000 100%	>225 000 0%	>250 000 0%	>310 000 0%	>380 000 0%	44
IP SLA G 711u [10.0.3.252->62.61.7.2] PacketLoss (%)	<=1 43,2%	>1 13,6%	>2 6,82%	>3 9,09%	>5 27,3%	44
IP SLA G 711u [10.0.3.252->62.61.7.2] Jitter (usec)	<=50 000 36,4%	>50 000 36,4%	>60 000 18,2%	>80 000 9,09%	>100 000 0%	44
IP SLA G 711u [10.0.3.252->62.61.7.2] The Number of Round Trip Operations	>=95 6,82%	<95 22,7%	<85 9,09%	<70 11,4%	<50 50%	44
	IP- ()	0%	0%	2,27%	22,7%	44

ProLAN; +7 (495) 933-12-89, (495) 913-30-67, sales@prolan.ru. (www.prolan.ru/ta).

PROLAN: PROLAN, : PARTNER@PROLAN.RU.

ЭЛИТАРНОЕ ДОСТУПНО



www.prolan.ru/services

(C) ProLAN 2008, www.prolan.ru

